

LINE BEARING DISTANCE

L-1 S 68-38-26 E 339.783
L-2 N 27-48-20 E 57.251
L-3 N 18-50-22 E 108.769
L-4 N 10-42-45 E 63.333
L-5 N 28-25-04 W 25.882
L-6 N 69-03-44 W 27.853
L-7 N 78-50-11 W 35.954
L-8 N 84-02-06 W 78.333
L-9 S 4-57-45 W 31.896

CENTERLINE PIPELINE
RIGHT-OF-WAY

SMITH 2-6C5
Well Location

SEC 1 SEC 6
SEC 12 SEC 7
N 88°02'05"E
2431.48'
911.82'
S 88°24'54"E
2630.67'

Found Duchesne
County Monument
at Sec. Cor.

Found original
stone corner at 1/4 Cor.
Set 2 1/2" dia. aluminum
County monument.

Found original
stone corner at
Sec. Cor. Set 2 1/2" dia.
aluminum County
monument.

LINE BEARING DISTANCE

P-1 N 38-03-44 W 872.793
P-2 N 44-47-01 W 636.623
P-3 N 51-01-10 W 399.202
P-4 N 60-45-16 W 108.242
P-5 N 51-32-34 W 490.274
P-6 N 53-26-15 W 306.436
P-7 N 47-12-54 W 239.847
P-8 N 25-37-07 W 102.504
P-9 S 85-53-42 W 137.948
P-10 S 83-19-59 W 163.857
P-11 N 8-16-36 W 146.447
P-12 N 4-17-11 E 108.044
P-13 N 10-33-36 W 63.986
P-14 N 18-21-26 W 49.545
P-15 N 37-21-55 W 66.057
P-16 N 57-35-55 W 242.868
P-17 N 49-33-37 W 105.464
P-18 N 40-44-26 W 110.674
P-19 N 34-48-36 W 99.689
P-20 N 51-21-32 W 83.510
P-21 N 57-33-30 W 96.557
P-22 N 62-56-14 W 116.263
P-23 N 55-56-17 W 179.205
P-24 N 39-53-27 W 93.342
P-25 N 27-56-24 W 124.445
P-26 N 16-30-42 W 94.371
P-27 N 5-58-55 W 73.034
P-28 DELTA: 93-14-25
R= 188.000 A= 305.942
C= 273.283 T= 198.945
P-29 S 74-35-09 E 120.016

CENTERLINE PIPELINE
RIGHT-OF-WAY

1"=300'

S 0°02'21"E
2633.99'

Found original
stone corner at
1/4 Cor. Set 2 1/2" dia.
aluminum County
monument.

Found County
monument at
Sec. Cor.

SEC 7 SEC 8
SEC 18 SEC 17

9 Nov '92 87-121-029

PIPELINE RIGHT-OF-WAY SURVEY FOR

ANR PRODUCTION COMPANY

SECS 6 & 7, TOWNSHIP 3 SOUTH, RANGE 5 WEST
UINTAH SPECIAL BASE AND MERIDIAN


DESCRIPTION OF RIGHT-OF-WAY

A 30 feet wide right-of-way over part of Sections 6 and 7, Township 3 South, Range 5 West of the Uintah Special Base and Meridian, the centerline of said right-of-way being further described as follows: Beginning at a point which is South 31°27'41" West 489.63 feet from the East Quarter Corner of said Section 7;
Thence North 38°03'44" West 872.79 feet;
Thence North 44°47'01" West 636.62 feet;
Thence North 51°01'10" West 399.20 feet;
Thence North 60°45'16" West 108.24 feet;
Thence North 51°32'34" West 490.27 feet;
Thence North 53°26'15" West 306.44 feet;
Thence North 47°12'54" West 239.85 feet;
Thence North 25°37'07" West 102.50 feet;
Thence South 85°53'42" West 137.95 feet;
Thence South 83°19'59" West 163.86 feet;
Thence North 8°16'36" West 146.45 feet;
Thence North 4°17'11" East 108.04 feet;
Thence North 10°33'36" West 63.99 feet;
Thence North 18°21'26" West 49.55 feet;
Thence North 37°21'55" West 66.06 feet;
Thence North 57°35'55" West 242.87 feet;
Thence North 49°33'37" West 105.46 feet;
Thence North 40°44'26" West 110.67 feet;
Thence North 34°48'36" West 99.69 feet;
Thence North 51°21'32" West 83.51 feet;
Thence North 57°33'30" West 96.56 feet;
Thence North 62°56'14" West 116.26 feet to the North line of said Section 7;
Thence North 55°56'17" West 179.21 feet;
Thence North 39°53'27" West 93.34 feet;
Thence North 27°56'24" West 124.45 feet;
Thence North 16°30'42" West 94.37 feet;
Thence North 5°58'55" West 73.03 feet;
Thence Northerly 305.94 feet along a curve to the right having a central angle of 93°14'25" and a radius of 188.00 feet;
Thence South 74°35'09" East 120.02 feet to the Smith 2-6C5 well location, said described centerline being 5737.19 feet in length and containing 3.95 acres.


SURVEYOR'S CERTIFICATE

This is to certify that I have surveyed the right-of-way shown on this plat, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.

Jerry D. Allred
Jerry D. Allred, Registered Land
Surveyor, Cert. No. 3817 (Utah)



31 Dec '92 Duchesne County Surveyor's File # 264



JERRY D. ALLRED & ASSOCIATES
Surveying & Engineering Consultants
121 North Center Street
P.O. Drawer C
Duchesne, Utah 84021
(801) 738-5352